

**BUILDING TRUST** 

# PRODUCT DATA SHEET Sika® Stabilizer-100 LK

## VISCOSITY MODIFYING ADMIXTURE

#### DESCRIPTION

Sika<sup>®</sup> Stabilizer-100 LK is a concrete admixture that increases the stability and cohesiveness of concrete and mortar mixes. It has been specially developed for Self Compacting Concrete (SCC). Sika<sup>®</sup> Stabilizer-100 LK also improves the fresh concrete properties of mixes with varying fines content, low cement content or concrete mixes with unfavourable grading curves.

#### USES

- Self Compacting Concrete (SCC)
- Shotcrete applications
- Pumped concrete
- Where stability during transportation and placing is required
- Low fines content concrete

## **PRODUCT INFORMATION**

#### **CHARACTERISTICS / ADVANTAGES**

- Increases mix cohesiveness
- Lower sensitivity against variations in the constituent materials
- Good mix consistency
- Reduces bleeding
- Lower tendency to segregation
- Reduction of compaction defects
- Smoother concrete surfaces
- Improved pumpability
- Suitable for use in reinforced and pre-stressed concrete
- Does not contain chlorides or any other substances which promote steel corrosion

Composition	Modified lignosulphonate
Packaging	1000 L, IBC
Appearance / Colour	Dark Brown liquid
Shelf life	12 months if stored properly in original unopened packaging
Storage conditions	Stored in dry conditions, protected from direct sunlight and at temperat?ures between +5 °C and 40 °C
Density	1.17 ± 0.03 kg/l (at 25 °C)

### **APPLICATION INFORMATION**

Recommended dosage	0.2 - 0.5 % by weight of cement
Compatibility	Sika® Stabilizer-100 LK may be combined with many other Sika® products. Combination with other admixtures may affect the amount of air entrained into the concrete. Trials must always be carried out before com- bining products in specific mixes. Contact Sika Technical Services for addi- tional information and any specific combinations.
Dispensing	Sika <sup>®</sup> Stabilizer-100 LK must be measured using suitable equipment then mixed with the batching gauging water or both added together at the same time into the batching plant concrete mixer. It may also be added to the concrete in the drum of a ready mix truck at the jobsite. In this case, an additional mixing time of at least 1 minute per m3 of concrete must be completed before placement.
Restrictions	Sika® Stabilizer-100 LK must not be added to dry cement. Overdosing may result in retardation. For optimum dosage, trials are recommended.

#### **BASIS OF PRODUCT DATA**

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

# ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

# LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Lanka (Private) Limited No. 58/12-B Raja Mawatha Ekala, Ja-Ela Sri Lanka



**PRODUCT DATA SHEET Sika® Stabilizer-100 LK** July 2021, Version 01.01 021404021000000170 SikaStabilizer-100LK-en-LK-(07-2021)-1-1.pdf

BUILDING TRUST

